

QObject	
staticMetaObject	staticQtMetaObject
staticMetaObject	ExtraData
d_ptr	
metaObject	connect
qt_metacast	connect
tr	disconnect
trUtf8	disconnect
tr	disconnect
trUtf8	disconnect
qt_metacall	dumpObjectTree
qt_static_metacall	dumpObjectInfo
d_func	setProperty
d_func	property
QObject	dynamicPropertyNames
@~QObject	registerUserData
event	setUserData
eventFilter	userData
objectName	destroyed
setObjectName	parent
isWidgetType	inherits
signalsBlocked	deleteLater
blockSignals	sender
thread	senderSignalIndex
moveToThread	receivers
startTimer	timerEvent
killTimer	childEvent
children	customEvent
setParent	connectNotify
installEventFilter	disconnectNotify
removeEventFilter	QObject
connect	

QCoreApplication	
staticMetaObject	UnicodeUTF8
staticMetaObject	DefaultCodec
ApplicationFlags	self
CodecForTr	
metaObject	sendPostedEvents
qt_metacast	sendPostedEvents
tr	removePostedEvent
trUtf8	removePostedEvent
tr	hasPendingEvents
trUtf8	notify
qt_metacall	startingUp
qt_static_metacall	closingDown
d_func	applicationDirPath
d_func	applicationFilePath
QCoreApplication	applicationPid
@~QCoreApplication	libraryPaths
argc	libraryPaths
argv	addLibraryPath
arguments	removeLibraryPath
setAttribute	installTranslator
testAttribute	removeTranslator
setOrganizationDomain	translate
organizationDomain	translate
setOrganizationName	flush
organizationName	watchUnixSignal
setApplicationName	setEventFilter
applicationName	filterEvent
setApplicationVersion	version
applicationVersion	aboutToQuit
instance	unixSignal
exec	event
processEvents	compressEvent
processEvents	QCoreApplication
exit	sendSpontaneousEvent
sendEvent	notifyInternal
postEvent	init
postEvent	

QApplication		
staticMetaObject	GuiClient	CustomColor
staticMetaObject	DBusServer	ManyColor
Tty	NormalColor	
metaObject	topLevelWidgets	isLeftToRight
qt_metacast	desktop	isEffectEnabled
tr	activePopupWidget	setEffectEnabled
trUtf8	activeModalWidget	setEventFilter
tr	clipboard	x11ClientMessage
trUtf8	focusWidget	x11ProcessEvent
qt_metacall	activeWindow	isSessionRestored
qt_static_metacall	setActiveWindow	sessionId
QApplication	widgetAt	sessionKey
QApplication	widgetAt	commitData
QApplication	topLevelAt	saveState
QApplication	topLevelAt	setInputContext
QApplication	syncX	inputContext
@~QApplication	beep	keyboardInputLocale
type	alert	keyboardInputDirection
style	keyboardModifiers	exec
setStyle	queryKeyboardModifiers	
setStyle	mouseButtons	setQuitOnLastWindowClosed
colorSpec	setDesktopSettingsAware	setQuitOnLastWindowClosed
setColorSpec	desktopSettingsAware	setWindowClosed
setGraphicsSystem	setCursorFlashTime	focusChanged
overrideCursor	cursorFlashTime	fontDatabaseChanged
setOverrideCursor	setDoubleClickInterval	commitDataRequest
changeOverrideCursor	setDoubleClickInterval	saveStateRequest
restoreOverrideCursor	setKeyboardInputStyleSheet	
palette	keyboardInputIntents	styleSheet
palette	setWheelScrollLines	setAutoSipEnabled
palette	wheelScrollLines	autoSipEnabled
setPalette	setGlobalStrut	closeAllWindows
font	globalStrut	aboutQt
font	setStartDragTime	event
font	startDragTime	compressEvent
setFont	setStartDragDistance	QApplication
fontMetrics	startDragDistance	operator=
setWindowIcon	setLayoutDirection	
windowIcon	layoutDirection	
allWidgets	isRightToLeft	

QCoreApplication
staticMetaObject
staticMetaObject
ExtraData
fQTimer
fRTimer
fgDebug
fgWarning
fgIsA